



RPB Series Pendant Station - Rubber Enclosures

One-Speed and Two-Speed Control plus Accessories
With Standard Cord Grip



RP-4



RP-3



RP-2



RP-1

Dimensions and Weights

Enclosure Size	Dimension-Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
Two-Button	3	2-1/2	5-3/4	1-3/4	.437 - .740
Four-Button	3	2-1/2	9	2-3/4	.437 - .740
Six-Button	3	2-1/2	12-3/8	3-1/2	.437 - .740
Eight-Button	3	2-5/8	15-3/4	4-1/4	.640 - .875

*** Specify Cable Diameter when the Cable Used is not within the Range Listed.**

RPB Series Pushbutton Pendant Stations feature steel reinforced rubber construction with a tongue and groove cover plate to protect buttons from many elements. The RPB Series support a number of applications with single and two speed operation, momentary and maintained switches, and a variety of accessory and replacement parts. Wire mesh grips for added strain relief are available.

- Nitrile Rubber Construction
- NEMA 1, 3, 4 and 12
- CSA Approved

Enclosures

Each complete enclosure includes a standard package of legend plates, cord grip and strain relief bracket.

- | | |
|------|--------------|
| RP-1 | Two-Button |
| RP-2 | Four-Button |
| RP-3 | Six-Button |
| RP-4 | Eight-Button |

Front Covers Only (including Legend Plate Package)

- | | |
|-------|--------------|
| RP-1F | Two-Button |
| RP-2F | Four-Button |
| RP-3F | Six-Button |
| RP-4F | Eight-Button |

Pictures are for illustration purposes and may not represent actual product.
Duct-O-Wire® recommends installation of an Emergency Stop on all Pendants.

